



GreenChoice

- Sustainable design using rapidly renewable materials
- FSC factory certified
- Indoor air quality rated



Easy Care

- Stable-Guard Core: enhanced visual and structural integrity
- Sweep N' Go no wax floor care
- · Scratch, scuff and stain resistant
- PEARLTOUCH™x is an advanced 9 layer UV cured Urethane and Aluminum Oxide finish. This technology gives you a clean, yet slightly textured satin like finish.



Option Plus

- Uniclic, and patented Drop-Loc installation
- Residential and selected commercial below, on or above grade applications
- Float-in or glue down install
- Radiant heat approved



27 Year Warranty

- 27 year Residential Finish
- 3 year Light Commercial
- Limited Lifetime Structure



enhanced


MERICANA WIDE



Cayenne Maple | MW04H



Toffee Maple | MW313H



Cinnamon Spice Oak MW03H I MW03WBH



Smoked Maple I MW315H



Americano Maple I MW316H



Caramel Brulee Oak MW604WBH

specifications

*WB = Wire Brush

SUPPLIER

Kraus®

CONSTRUCTION	PROFILE	SPECIES	TYPE	FINISH	LOCKING SYSTEM	VISUAL	COLOUR VARIATIONS
3/8"	5"	Oak and Maple	Engineered	Smooth and Wire brushed	Uniclic and Drop-Loc	4 Edge Micro	Medium
TRIM OPTIONS							



Wall Base



Quarter Round



T-mold



Multi-purpose Reducer



Threshold



Stair Nose

carton configuration

Plank Size: 3/8" x 5" x Random Length (12" to 47") | Packaging: 16.40 sq.ft/carton | Packaging: 22.05 lbs/carton

27 year warranty

27 Year Residential Finish | 3 Year Light Commercial Finish | Limited Lifetime Structure

important information about hardwood floors

Wood is a natural product containing natural characteristics such as variations in colour, tone and graining. Some variation in colour and small sound knots is to be expected in a natural wood floor. Please note that the display sample may not always be a true representation of the final wood product. For this reason, new and/or replacement flooring may not exactly match display samples and/or existing flooring. A natural wood floor is subject to colour changes with the exposure to normal sunlight. These colour changes should be expected and are a desired attribute in the uniqueness of a wood floor.

